

Mode 3: Parameter table of fixed AC charging

www.afore.it

Model	TB-AC3221EUH-SOCKET0	TB-AC3221EUH-SOCKET1	TB-AC3221EUH-SOCKET-TY
Standard	EU	EU	EU
Power	7kW	11/22kW	11/22kW
Input Voltage/Output Voltage	400VAC/400VAC	400VAC/400VAC	400VAC/400VAC
Input frequency	50/60Hz	50/60Hz	50/60Hz
Output current	32A	16A/32A adjustable	16A/32A adjustable
Rated residual operating current	TypeA+DC6mA	TypeA+DC6mA	TypeA+DC6mA
Over temperature protection	≥95°C	≥95°C	≥95°C
Mean time between failure	MTBF≥8796h	MTBF≥8796h	MTBF≥8796h
Charging start mode	Plug and play,RFID,APP	Plug and play,RFID,APP	Plug and play,RFID,APP
APP/Communication	Support/WIFI/BLE/4G Optional	Support/WIFI/BLE/4G Optional	Support/WIFI/BLE/4G Optional
Relative humidity	5%~95% No condensation	5%~95% No condensation	5%~95% No condensation
Maximum altitude	2000m	2000m	2000m
Life time of connector	≥10000 times	≥10000 times	≥10000 times
Operating /Storage temperature	-30°C~+50°C/-40°C~+85°C	-30°C~+50°C/-40°C~+85°C	-30°C~+50°C/-40°C~+85°C
Cable length	5 meters (Customizable)	5 meters (Customizable)	5 meters (Customizable)
Wiring method	Enter and out at the bottom	Enter and out at the bottom	Enter and out at the bottom
Connector type	IEC 62196-2 Type 2	IEC 62196-2 Type 2	IEC 62196-2 Type 2
User Interface	LED indicator	LED indicator+ LCD screen / LED indicator	Screen selectable
Weight	1.8 Kg (cable not included)	1.8 Kg (cable not included)	1.8 Kg (cable not included)
Color	White/Black/Dark Grey	White/Black/Dark Grey	White/Black/Dark Grey
Host dimension	311*192*80mm	311*192*80mm	311*192*80mm
Degree of protection	Charging Connector IP54,Host IP65/IK10		



FEATURES:

- Support smart APP Operating with OCPP 1.6
- Charging start mode: Plug and Play/RFID/APP
- Max 32A - 7KW/22KW
- Multiple safety protection include short circuit, over current, over voltage, Under-voltage, leakage, lightning, Over temperature protection

